

(12) **United States Patent**
Nagler

(10) **Patent No.:** **US 9,637,074 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **DRIVE ARRANGEMENT IN A MOTOR VEHICLE**

(75) Inventor: **Toni Nagler**, Bamberg (DE)

(73) Assignee: **Brose Fahrzeugteile GmbH & Co. KG, Hallstadt**, Hallstadt (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 863 days.

(21) Appl. No.: **13/989,364**

(22) PCT Filed: **Nov. 17, 2011**

(86) PCT No.: **PCT/EP2011/005788**

§ 371 (c)(1),
(2), (4) Date: **Aug. 9, 2013**

(87) PCT Pub. No.: **WO2012/069159**

PCT Pub. Date: **May 31, 2012**

(65) **Prior Publication Data**

US 2013/0342010 A1 Dec. 26, 2013

(30) **Foreign Application Priority Data**

Nov. 23, 2010 (DE) 10 2010 052 045

(51) **Int. Cl.**
B60L 1/00 (2006.01)
B60L 3/00 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **B60R 16/03** (2013.01); **H02P 5/68** (2013.01); **H02P 7/04** (2016.02); **E05F 15/622** (2015.01);

(Continued)

(58) **Field of Classification Search**

CPC B60R 16/03; H02P 7/0044; H02P 5/68
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,593,711 B2 * 7/2003 Brereton B60L 11/1805
318/34

8,766,563 B2 7/2014 Eggelin et al.
(Continued)

FOREIGN PATENT DOCUMENTS

DE 19639252 11/1997
EP 1154557 11/2001

(Continued)

OTHER PUBLICATIONS

International Preliminary Report on Patentability, for PCT/EP2011/005788 corresponding to U.S. Appl. No. 13/989,364, mailed May 28, 2013 (12 pages) with translation.

(Continued)

Primary Examiner — Rexford Barrie

Assistant Examiner — Rasem Mourad

(74) *Attorney, Agent, or Firm* — Pauly, Devries, Smith & Deffner, LLC

(57) **ABSTRACT**

The invention relates to a drive arrangement in a motor vehicle, wherein a first drive, a second drive and a third drive are provided, wherein the drives each have two supply connections, and wherein the first drive and the second drive each have their own associated driver circuit. The invention proposes that the supply connections of the third drive can be connected to high potential (V_+) and low potential (V_-) by means of the two driver circuits.

10 Claims, 4 Drawing Sheets

